





TECHNISCHE SPECIFICATIES SACH UNITS

				
<b>Technisch overzicht</b>	<b>New Concept</b>	<b>Dynamic 1.6</b>	<b>Dynamic 1.8</b>	<b>Dynamic 2.4</b>
Prijs €	550	675	845	1.045
Wattage	1300	1600	1800	2400
Stroomsterkte	6.17 A	6.44 A	7.20 A	7.85 A
Spanning	220V 240V	220V 240V	220V 240V	220V 240V
Onderdruk in mm waterkolom	2600	3100	3300	2800
Luchtverplaatsing ltr/pm	3500	3160	3555	4900
Filtersysteem	Stofzak	Cyclonisch	Cyclonisch	Cyclonisch
Vuilcontainer inhoud	5L	20L	28L	28L
Oververhittingsbeveiliging	X	X	X	X
Akoestische motor		X	X	X
Afvoer naar buiten noodzakelijk	X			
Aantal luchtinlaten	2	1	1	1
Aantal luchtuitlaten	1	1	1	2
Aantal motoren	1	1	1	2
Plaatsing motoren				Parallel
2-stage motor bypass	X	X	X	X
Geluid (dB)	61	60	60	60
Gewicht in KG	8	15	16	17
Kleur	Grijs	Beige/ oranje	Beige/ oranje	Beige/ oranje
Afmeting h-b-d	48-42-23	82-39-38	92-39-38	92-39-38
Pro-Tecta filtersysteem		X	X	X
CE-keur	X	X	X	X
Max. afstand van motorunit naar zuiginlaten	25m	30m	50m	60m
Maximum aantal zuiginlaten	4	8	12	20